



No. Z2 15 06 59417 033

Buk 29
72-003 Dobra
POLAND





Product Service

CERTIFICATE**No. Z2 15 06 59417 033**

Model(s): 1601b, 1601s, 1602b,
1602s, 1606, 1615, 1642

Parameters: Type 1601b single swing with cradle swing seat
Type 1601s single swing with board swing seat
Type 1602b double swing with cradle swing seat
Type 1602s double swing with board swing seat
Type 1606 single swing with board swing seat
Type 1615 net swing

The swings are comprised of steel tubes with two A-supports. The crossbar \varnothing 88.9 X 3,6 mm is welded with steel arches, onto which the posts \varnothing 88.9 X 3.6 mm are attached and screwed together with transit bolts. 4 mm thick metal plates for holding the swing hinges are welded to the crossbar.

Total height:	2.27 m
Total depth:	1.95 m

Single swing:	
Total width	2.13 m
Double swing:	
Total width	3.33 m

Single swing:	
Total height	2.16 m
Height of the swing bearing	2.00 m
Width	2.59 m

1642
The equipment is comprised of a seesaw, with shock absorbers integrated into the bearing, and a swing. The swing is comprised of a post \varnothing 139.7 X 4 mm inclined at an angle (22°), which has been angled at the top at an angle of 68° to the horizontal. The swing is suspended at the angled end. The seesaw axle with the bearing is welded to the post of the swing.

Total width:	2.80 m
Length	3.24 m
Height:	2.32 m

Tested according to: EN 1176-1:2008
EN 1176-2:2008

Production Facility(ies): 59417

Page 2 of 2